

Advanced Linux Usage

2019-09-10

Anders Sjölander
anders.sjolander@uppmx.uu.se

Enabler for Life Sciences

- Same program, many files

```
$ ls -l
total 0
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_1.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_2.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_3.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_4.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_5.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_6.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_7.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_8.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_9.bam
$ my_prog sample_1.bam
```

- Same program, many files

```
$ ls -l
total 0
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_1.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_2.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_3.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_4.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_5.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_6.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_7.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_8.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_9.bam
$ my_prog sample_1.bam
$ my_prog sample_2.bam
```

- Same program, many files

```
$ ls -l
total 0
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_1.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_2.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_3.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_4.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_5.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_6.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_7.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_8.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 16:42 sample_9.bam
$ my_prog sample_1.bam
$ my_prog sample_2.bam
$ my_prog sample_3.bam
$ my_prog sample_4.bam
$ my_prog sample_5.bam
$ my_prog sample_6.bam
$ my_prog sample_7.bam
$ my_prog sample_8.bam
$ my_prog sample_9.bam
$
```

Multiple files

- Same program, many files
 - 10 files? Ok
 - 1000 files? Not ok

Multiple files

- Same program, many files
 - 10 files? Ok
 - 1000 files? Not ok
- Reproducibility
 - Self and others

Multiple files

- Same program, many files
 - 10 files? Ok
 - 1000 files? Not ok
- Reproducibility
 - Self and others

A solution - write a script!


```
total 0
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_1.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_2.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_3.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_4.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_5.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_6.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_7.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_8.bam
-rw-rw-r-- 1 dahlo dahlo 0 Sep  1 17:18 sample_9.bam
$ nano analysis.sh
```

^G Get Help
^X Exit

^O WriteOut
^J Justify

^R Read File
^W Where Is

^Y Prev Page
^V Next Page

^K Cut Text
^U UnCut Text

^C Cur Pos
^T To Spell

GNU nano 2.0.9

File: analysis.sh

Modified

my_prog sample_1.bam

^G Get Help
^X Exit

^O WriteOut
^J Justify

^R Read File
^W Where Is

^Y Prev Page
^V Next Page

^K Cut Text
^U UnCut Text

^C Cur Pos
^T To Spell

GNU nano 2.0.9

File: analysis.sh

Modified

```
my_prog sample_1.bam  
my_prog sample_2.bam
```

^G Get Help
^X Exit

^O WriteOut
^J Justify

^R Read File
^W Where Is

^Y Prev Page
^V Next Page

^K Cut Text
^U UnCut Text

^C Cur Pos
^T To Spell

GNU nano 2.0.9

File: analysis.sh

Modified

```
my_prog sample_1.bam  
my_prog sample_2.bam  
my_prog sample_3.bam  
my_prog sample_4.bam  
my_prog sample_5.bam  
my_prog sample_6.bam  
my_prog sample_7.bam  
my_prog sample_8.bam  
my_prog sample_9.bam
```

^G Get Help
^X Exit

^O WriteOut
^J Justify

^R Read File
^W Where Is

^Y Prev Page
^V Next Page

^K Cut Text
^U UnCut Text

^C Cur Pos
^T To Spell

```
$ l
total 4,0K
-rw-rw-r-- 1 dahlo dahlo 267 Sep  7 09:34 analysis.sh
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_1.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_2.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_3.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_4.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_5.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_6.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_7.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_8.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_9.bam
$
```

```
$ l
total 4,0K
-rw-rw-r-- 1 dahlo dahlo 267 Sep  7 09:34 analysis.sh
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_1.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_2.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_3.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_4.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_5.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_6.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_7.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_8.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_9.bam
$ bash analysis.sh
```

```
$ l
total 4,0K
-rw-rw-r-- 1 dahlo dahlo 267 Sep  7 09:34 analysis.sh
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_1.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_2.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_3.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_4.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_5.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_6.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_7.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_8.bam
-rw-rw-r-- 1 dahlo dahlo   0 Sep  1 17:18 sample_9.bam
$ bash analysis.sh
```

Still not OK for 1000 or more files!

GNU nano 2.0.9

File: analysis.sh

Modified

```
my_prog sample_1.bam  
my_prog sample_2.bam  
my_prog sample_3.bam  
my_prog sample_4.bam  
my_prog sample_5.bam  
my_prog sample_6.bam  
my_prog sample_7.bam  
my_prog sample_8.bam  
my_prog sample_9.bam
```

^G Get Help
^X Exit

^O WriteOut
^J Justify

^R Read File
^W Where Is

^Y Prev Page
^V Next Page

^K Cut Text
^U UnCut Text

^C Cur Pos
^T To Spell

GNU nano 2.5.3

File: analysis.sh

```
my_prog -r references/human_genome.fa sample_1.bam
my_prog -r references/human_genome.fa sample_2.bam
my_prog -r references/human_genome.fa sample_3.bam
my_prog -r references/human_genome.fa sample_4.bam
my_prog -r references/human_genome.fa sample_5.bam
my_prog -r references/human_genome.fa sample_6.bam
my_prog -r references/human_genome.fa sample_7.bam
my_prog -r references/human_genome.fa sample_8.bam
my_prog -r references/human_genome.fa sample_9.bam
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

- **Assigning**

```
my_variable=5
```

```
my_variable="nice text"
```

- **Assigning**

```
my_variable=5
```

```
my_variable="nice text"
```

- **Using**

```
$my_variable
```

- **Assigning**

```
my_variable=5
```

```
my_variable="nice text"
```

- **Using**

```
$my_variable
```

```
$ my_variable="Dave"
```

- **Assigning**

```
my_variable=5
```

```
my_variable="nice text"
```

- **Using**

```
$my_variable
```

```
$ my_variable="Dave"
```

```
$ echo "Hello, $my_variable."
```

- **Assigning**

```
my_variable=5
```

```
my_variable="nice text"
```

- **Using**

```
$my_variable
```

```
$ my_variable="Dave"
```

```
$ echo "Hello, $my_variable."
```

```
Hello, Dave.
```

GNU nano 2.5.3

File: analysis.sh

```
my_prog -r references/human_genome.fa sample_1.bam
my_prog -r references/human_genome.fa sample_2.bam
my_prog -r references/human_genome.fa sample_3.bam
my_prog -r references/human_genome.fa sample_4.bam
my_prog -r references/human_genome.fa sample_5.bam
my_prog -r references/human_genome.fa sample_6.bam
my_prog -r references/human_genome.fa sample_7.bam
my_prog -r references/human_genome.fa sample_8.bam
my_prog -r references/human_genome.fa sample_9.bam
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

GNU nano 2.5.3

File: analysis.sh

```
ref=references/human_genome.fa
```

```
my_prog -r $ref sample_1.bam  
my_prog -r $ref sample_2.bam  
my_prog -r $ref sample_3.bam  
my_prog -r $ref sample_4.bam  
my_prog -r $ref sample_5.bam  
my_prog -r $ref sample_6.bam  
my_prog -r $ref sample_7.bam  
my_prog -r $ref sample_8.bam  
my_prog -r $ref sample_9.bam
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

[Read 12 lines]

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
```

```
my_prog -r $ref sample_1.bam  
my_prog -r $ref sample_2.bam  
my_prog -r $ref sample_3.bam  
my_prog -r $ref sample_4.bam  
my_prog -r $ref sample_5.bam  
my_prog -r $ref sample_6.bam  
my_prog -r $ref sample_7.bam  
my_prog -r $ref sample_8.bam  
my_prog -r $ref sample_9.bam
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

```
for var in 1 2 3;  
do  
    echo $var  
done
```

```
$ bash loop_test.sh  
1  
2  
3  
$
```

```
for var in text works too;  
do  
    echo $var  
done
```

```
$ bash loop_test.sh  
text  
works  
too  
$
```

```
for var in mix them 5;  
do  
    echo $var  
done
```

```
$ bash loop_test.sh  
mix  
them  
5  
$
```

```
for var in *.txt;  
do  
    echo $var  
done
```

```
$ bash loop_test.sh  
all.txt  
examples.txt  
readme.txt
```

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
```

```
my_prog -r $ref sample_1.bam  
my_prog -r $ref sample_2.bam  
my_prog -r $ref sample_3.bam  
my_prog -r $ref sample_4.bam  
my_prog -r $ref sample_5.bam  
my_prog -r $ref sample_6.bam  
my_prog -r $ref sample_7.bam  
my_prog -r $ref sample_8.bam  
my_prog -r $ref sample_9.bam
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
for file in *.bam ;
do
    my_prog -r $ref $file
done
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa  
for file in *.bam ;  
do  
    echo my_prog -r $ref $file  
done
```

Debugging!

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
for file in *.bam ;
do
    echo my_prog -r $ref $file
done
```

```
$ bash analysis.sh
my_prog -r references/goat_genome_version4.1.fa sample_1.bam
my_prog -r references/goat_genome_version4.1.fa sample_2.bam
my_prog -r references/goat_genome_version4.1.fa sample_3.bam
my_prog -r references/goat_genome_version4.1.fa sample_4.bam
my_prog -r references/goat_genome_version4.1.fa sample_5.bam
my_prog -r references/goat_genome_version4.1.fa sample_6.bam
my_prog -r references/goat_genome_version4.1.fa sample_7.bam
my_prog -r references/goat_genome_version4.1.fa sample_8.bam
my_prog -r references/goat_genome_version4.1.fa sample_9.bam
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Te

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
```

```
for file in *.bam ;  
do  
    my_prog -r $ref $file  
done
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

Basic script

```
$ bash analysis.sh
```

```
$ bash analysis.sh data/
```

```
$ bash analysis.sh data/
```

```
$1
```

```
$ bash analysis.sh data/ second_argument
```

\$1

\$2

```
$ bash analysis.sh data/ second_argument third
```

\$1

\$2

\$3

Basic script

```
$ bash analysis.sh data/ second_argument third "fourth argument"
```

\$1

\$2

\$3

\$4

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
for file in *.bam ;
do
    my_prog -r $ref $file
done
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa  
for file in $1/*.bam ;  
do  
    my_prog -r $ref $file  
done
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

```
$ cat file.list  
sample_1.bam  
sample_3.bam  
smample_9.bam
```

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
for file in $1/*.bam ;
do
    my_prog -r $ref $file
done
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
for file in $( cat $1 ) ;
do
    my_prog -r $ref $file
done
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^J Justify
^T To Spell

^C Cur Pos
^_ Go To Line

^Y Prev Page
^V Next Page

Basic script

GNU nano 2.5.3

File: analysis.sh

```
ref=references/goat_genome_version4.1.fa
```

```
for file in $( cat $1 ) ;  
do  
    my_prog -r $ref $file  
done
```

```
$ cat file.list  
sample_1.bam  
sample_3.bam  
sample_9.bam  
$ bash analysis.sh file.list
```

^G Get Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut Text
^U Uncut Text

^
^

- Control statement

```
if condition; then  
    action  
fi
```


- Control statement

```
if true; then  
    echo "This is true"  
fi
```

result:
This is true

- Control statement

```
if false; then  
  echo "This is true"  
fi
```

result:

- Control statement

```
if [[ 5 < 9 ]]; then  
    echo "This is true"  
fi
```

result:
This is true

- Control statement

```
if [[ 5 > 9 ]]; then  
    echo "This is true"  
fi
```

result:

- Control statement

```
if [[ 5 == 9 ]]; then  
    echo "This is true"  
fi
```

result:

- Control statement

```
if [[ "Hello" == "Hello" ]]; then  
    echo "This is true"  
fi
```

result:

```
This is true
```

- Control statement

```
if [[ "Hello" == "Hi" ]]; then  
    echo "This is true"  
fi
```

result:

- Control statement

```
if [[ "Hello" == "Hel"* ]]; then  
    echo "This is true"  
fi
```

result:

```
This is true
```


- For all samples except dog

```
for file in $1/*.bam ;  
do  
    echo my_prog $file  
done
```

- For all samples except dog

```
for file in $1/*.bam ;  
do  
    if [[ ... != "dog"* ]]; then  
        echo my_prog $file  
    fi  
done
```

- For all samples except dog

```
for file in $1/*.bam ;  
do  
    if [[ ... != "dog"* ]]; then  
        echo my_prog $file  
    fi  
done
```

Ex: `$file` is `/path/to/dog_1.bam`

- For all samples except dog

```
for file in $1/*.bam ;  
do  
    if [[ ... != "dog"* ]]; then  
        echo my_prog $file  
    fi  
done
```

Ex: `$file` is `/path/to/dog_1.bam`

`basename $file`

- For all samples except dog

```
for file in $1/*.bam ;
do
    if [[ ... != "dog"* ]]; then
        echo my_prog $file
    fi
done
```

Ex: `$file` is `/path/to/dog_1.bam`

```
basename $file
```

```
dog_1.bam
```

- For all samples except dog

```
for file in $1/*.bam ;
do
    if [[ $(basename $file) != "dog"* ]]; then
        echo my_prog $file
    fi
done
```

Ex: `$file` is `/path/to/dog_1.bam`

`basename $file`

`dog_1.bam`

- For all samples except dog

```
for file in $1/*.bam ;
do
    if [[ $(basename $file) != "dog"* ]]; then
        my_prog $file
    fi
done
```

Ex: `$file` is `/path/to/dog_1.bam`

`basename $file`

`dog_1.bam`

Different languages

- Programming is programming
 - Perl, Python, Bash, and more

- Programming is programming
 - Perl, Python, **Bash**, and more

```
for file in $1/*.bam ;  
do  
    if [[ $(basename $file) != "dog"* ]]; then  
        my_prog $file  
    fi  
done
```

- Programming is programming
 - **Perl**, Python, Bash, and more

```
for file in $1/*.bam ;
do
    if [[ $(basename $file) != "dog"* ]]; then
        my_prog $file
    fi
done
```

```
use strict;
use warnings;
use File::Basename;

foreach my $file (glob("$ARGV[0]/*.bam")) {
    if(basename($file) !~ "^dog.+"){
        system("my_prog", $file);
    }
}
```

- Programming is programming
 - Perl, **Python**, Bash, and more

```
for file in $1/*.bam ;
do
    if [[ $(basename $file) != "dog"* ]]; then
        my_prog $file
    fi
done
```

```
import glob
import sys
import subprocess
import os

for file in glob.glob( sys.argv[1] + "/*.bam" ):
    if not os.path.basename(file).startswith("dog"):
        subprocess.call( ["my_prog" , file] )
```

Different languages

- Programming is programming
 - Perl, Python, Bash, and more
- Start with one, git gud, (learn another)

Different languages

- Programming is programming
 - Perl, Python, Bash, and more
- Start with one, git gud, (learn another)

PYTHON


- Graphical text editor more similar to what you might be used to
- Launch through command line:

```
$ gedit
```

```
Open  [icon]  test.py  Save  [icon]  -  □  ×
~/work/tmp


A = "ACGT"
if len(A) <= 3:
    print("Sequence A is smaller or equal than 3.")
elif (len(A) > 3) and (len(A) < 5):
    print("Sequence A is greater than 3 and smaller than 5.")
elif len(A) == 5:
    print("Sequence A is equal to 5.")
else:
    print("Sequence A is greater than 5.")

Python  Tab Width: 4  Ln 4, Col 7  INS
```




```
1 A = "ACGT"
2 if len(A) <= 3:
3     print("Sequence A is smaller or equal than 3.")
4 elif len(A) > 3 and (len(A) < 5):
5     print("Sequence A is greater than 3 and smaller than 5.")
6 elif len(A) == 5:
7     print("Sequence A is equal to 5.")
8 else:
9     print("Sequence A is greater than 5.")
10
11
```

Python ▾ Tab Width: 4 ▾ Ln 4, Col 7 ▾ INS




```
1 A = "ACGT"
2 if len(A) <= 3:
3     print("Sequence A is smaller or equal than 3.")
4 elif len(A) > 3 and (len(A) < 5):
5     print("Sequence A is greater than 3 and smaller than 5.")
6 elif len(A) == 5:
7     print("Sequence A is equal to 5.")
8 else:
9     print("Sequence A is greater than 5.")
10
11
```



```
1 A = "ACGT"
2 if len(A) <= 3:
3     print("Sequence A is smaller or equal than 3.")
4 elif (len(A) > 3) and (len(A) < 5):
5     print("Sequence A is greater than 3 and smaller than 5.")
6 elif len(A) == 5:
7     print("Sequence A is equal to 5.")
8 else:
9     print("Sequence A is greater than 5.")
10
11
```

Python ▾ Tab Width: 4 ▾ Ln 4, Col 7 ▾ INS



```
1 A = "ACGT"
2 if len(A) <= 3:
3     print("Sequence A is smaller or equal than 3.")
4 elif (len(A) > 3) and (len(A) < 5):
5     print("Sequence A is greater than 3 and smaller than 5.")
6 elif len(A) == 5:
7     print("Sequence A is equal to 5.")
8 else:
9     print("Sequence A is greater than 5.")
10
11
```

Python ▾ Tab Width: 4 ▾ Ln 4, Col 7 ▾ INS

- Menu - Preferences - View
 - Display line numbers
 - Display overview map
 - Highlight current line
 - Highlight matching brackets
- Menu - Preferences - Editor
 - Tab width 4
 - Insert spaces instead of tabs
- Menu - Preferences - Fonts & Colors
 - Kate or Oblivion (or Monokai installed manually, google it)

- Laboratory time once again!